Ар	pproved For Release 2008/		810A007500300008	-1	25X1
COUNTRY_ *East G	. OLASSII TOATTON	FORN	PORT		
6	istration of the Aeroc	_	ONI		25X1
	٥				25X1
EVALUATION_	PLACE	OBTAINED			25 X ′
DATE OF CONTENT				i.	25 X 1
DATE OBTAINED		DATE PREPARED	6 July 1955	• .	
REFERENCES				: 1	
PAGES 2 3	ENCLOSURES (NO. & TYPE)	1 - sketch o	r litto		
REMARKS				*.	٠.
	This is UNE	VALUATED Informati	on	٠.	
				2	

VPL Pilot training.

In May 1955, a VPL officer

25X1

25X1

had to undergo a 6-month with a guard company. Subsequently, he was detached for technical trainign to the Kamenz school. His assignment to the flying personnel was at first refused because he had relatives in West Germany. In January 1955, however, it was approved. Subsequently, he had to undergo a medical and psycho-technical examination including the following tests:

25X1

25X1

25X1

The candidate had to sit in a completely blacked-out chamber while a red-white disc was rotated at high speed in front of his eyes. In this way, his capacity for reaction was determined. The reaction capacity of his ear was determined by means of a sequence of sounds transmitted at different pitches.

Theoretical training for student pilots comprised 12 subjects including navigation, instruction on the M-11 engine of the Yak-18, meteorology, radio operation (30 Morse code characters per minute), topography, aircraft theory etc. The marks given in the individual subjects ranged from 5 to 1, being the best mark. Only those students who were given marks 5 or 4 in the. theoretical subjects were admitted to flight training. The other students could repeat the examinations 2 weeks later. Military training of the flying personnel was conducted for about 2 hours per week. Flight training on two-seater aircraft was given on 3 days a week. At first, an instruction flight of 20 to 30 minutes' duration was made. Subsequently, 1 or 2 local flights were conducted, then horizontal flying in a specific training area, curvilinear flights and landings were practiced. The latter practices were made as follows: the aircraft came down for landing to 1 meter above the ground while extending landing gear and landing flaps and subsequently climbed again without landing. The altitude of the approach was gradually lowered until the first correct landing was made. Subsequently, 4 or 5 local flights were made and the lowering of the landing flaps was practiced After these flights, stunt and instrument flying were taken up. Formation flying was not practiced prior to May 1955.

The order for each take-off was given via radio. At first, the engine was run up on the dispersal l

SECRET				25X1
				25X_1
	•			
		_		



cir-to-ground radio sets were switched on by pressing the upper microphological degree gas control lever. The pilot reported:
"Ready for the gas control lever. The pilot reported:
"Ready for the cupon, the aircraft training including training on MiG-15. Alter a years. Theoretical training took about 3 months followed by training on Yak-18s that was scheduled to continue until October 1955. After an examination, instruction on weapons of the Yak-11 was planned to begin. The training course was said to conclude with practice flights on MiG-15s. 1

2. Technical details of the Yak-18 aircraft.

All Yak-18s are equipped with radio sets for sir-to-air and sir-to-ground communications and for intercommunication on the aircraft. The sets are switched on by 2 buttons on the gas control lever. The lower button enables intercommunication and the upper button is both for air-to-air and air-to-ground communications. The landing gear is operated by compressed air of 50 atm pressure. The extending mechanism can be set in three positions, i. e. for extending and retracting, riddle position and ventilation. The position of the landing gear is marked by a 4-lomp set with green and red light with an additional central button in case of failures. Another central is provided by a mechanical indicator on the upper side of the leading eage of the wing. The landing brakes have an hydraulic mechanism and are operated by foot at the pedal for the rudder control. A hand brake is additionally fitted on the control lever; it is synchronized with the rudder movement, that means, when the rudder is turned to the left, the left wheel will be braked when the brake is operated. The brakes can be applied from the seat of the flight instructor. The position of the landing flaps is controlled by a mechanical indicator. The feathering of the propeller is controlled automatically. At cruising speed, the average number of rotations is 1,200 per minute. The aircraft is equipped with a radio compass in order to take bearings of radio beacons while approaching and crossing over them. All aircraft used for fright training are equipped with seat-type parachutes. During the training course, a routine jump from an altitude of 1,500 meters must be made. The parachute is operated by hand and is also equipped with a pre-set mechanical release.

3. Pilot insignia for the VPL

In early June 1955, it was learned that, since 25 May 1955, the VEB Schloss-und Metallwarenfabriken Brandenburg (metal goods factories) have been working on tools required for the manufacture of metal insignia for the VPL. The insignia, about 12 cm long, allegedly represents 2 intended wings with a round metal disc in the middle. The disc is surrounded by an unsymmetrical oak leaf cluster and a black-red-golden cockade is in the middle of the disc. Both the rim of the disc and the wings are to be beaded. 2

1.	Comme	ent. The	present	report	which	dos	not	furnish	new	information	
	aszizem	details	on initia	al VPL j	pilot	train	ing.	•			

Comment. This is the first information on the manufacture of VPL insignia. For sketch of insignia, see Annex.

	,				
					25)
CRET			/	•	237
					25)

25X1


25X1

25X1

Approved For Release 2008/07/11: CIA-RDP80-00810A007500300008-7



SECP	E.T				ر ا
•	¥	-3-	 Annex		25
					2
$\overline{\Lambda}$	L Ins	ignia			



Approved For Release 2008/07/11 : CIA-RDP80-00810A007500300008-1

SECRET

25X1 25X1

Approved For Release 2008/07/11: CIA-RDP80-00810A007500300008-1 CLASSIFICATION Cast Cermany COUNTRY ___ Mainistration of the Mercelus EVALUATION_ PLACE OSTAINED 25X1 DATE OF CONTENT. DATE OBTAINED_ _DATE_PREPARED_ 25X1 REFERENCES____ ENCLOSURES (NO. & TYPE)_ PAGES____ REMARKS__ 25X1 This is UNEVALUATED Information 25X1 Val Pilot training. 25X1 In Law 1955, a VPL officer had to undergo a 6-month basic truining with a guard company: Subsequently, he was d tached for technical training to the Kamenz school. 25X1 His assignment to the flying pursonnel was at first refused because he had relatives in West Germany. In January 1955, however, it was approved. Subsequently, he had to undergo a medical and psycho-technical examination including the following tests: 25X1 The candidate had to sit in a condetely blacked-out chamber while a red-white disc was rotated at high speed in front of 25X1 his eyes. In this way, his caracity for reaction was determined The reaction capacity of his ear was determined by wears of a sequence of sounds transmitted at different bitches. Theoretical training for student pilets comprised 12 subjects including navigation, instruction on the N-11 engine of the Yak-18, meteorology, sudio operation (30 Morse code characters per minute), topography, discrait theory etc. The marks given in the individual subjects ranged from 5 to 3, being the best mark. Only those students who were given marks 5 or 4 in the theoretical subjects were admitted to flight training. The other students could repeat the examinations 2 weeks later. Military training of the flydage personnel was conducted for about 2 hours per week. Flight training on two-seater aircraft was given on Fdays a week. At first, an instruction flight of 20 to 30 minutes' duration was made. Subsequently, 1 or 2 local flights were conducted, then horizontal flying in a specific training area, curvilinear flights and landings were practiced. The latter practices were made as follows: the aircraft came ican for landing to a meter above the ground while extending landing gear and landing flaps and subsequently climbed again without landing. The altitude of the approach was grainably lowered until the first correct landing was made. Subsequently, 4 or 9 local flights were made and the lawsving of the landing flaps was presticed After these flights, stunt and instrument Clying were taken up. Formation flying was not practiced prior to Eay 1955 The order for each take-off was given vil radio. At first, the surplus was run up on the dispersal rane, then the instruments were checked and the CLASSIFICATION SECRAT 25X1 RI

.. 5 ...

)	ム	Y	1	
_	J	/\		

SEC	RET	

25X1

air to-ground radio sets were switched on by pressing the upper microphone button on the gas control lever. The pilot reported:
"Read; for flying". Thereupon, the aircraft training including training on MiC-15s allegedly lasted 3 years. Theoretical training took about 3 months followed by training on Yak-18s that was scheduled to continue until October 1955. After an examination, instruction on weapons of the Yak-11 was planned to begin. The training course was said to conclude with practice flights on MiC-15s. 1

2. Technical details of the lak-18 aircraft.

All Yak-18s are equipped with radio sets for air-to-air and air-to-ground communications and for in ercommunication on the aircraft. The sets are switched on by 2 buttons on the gas control lever. The lower button enables intercommunication and the upper button is both for air-to-air and air-to-ground communications. The landing gear is operated by compressed air of 50 abm pressure. The extending mechanism can be set in three positions; i. e. for extending and retracting, widdle position and ventilation. The position of the landing gear is marked by a 4-lamp set with green and red light with an additional control button in case of failures. Another control is provided by a mechanical indicator on the upper side of the leading edge of the wings The landing brakes have as hydraulic mechanism and are operated by foct at the pedal for the rudder control. A hand brake is additionally fitted on the control lever; it is synchronized with the rudder movement, that means, when the rudder is turned to the left, the left wheel will be braked when the brake is operated. The brakes can be applied from the seat of the flight instructor. The position of the landing flaps is controlled by a mechanical indicator. The feathering of the propeller is controlled automatically At cruising speed, the average number of rotations is 1,200 per minute. The aircraft is equipped with a radio compass in order to take bearings of radio beadons while approaching and crossing over them-All aircraft used for Phight training are equipped with seat-type parachutes. During the training course, .. routine jump from an altitude of 1,500 meters must be made. The parachute is operated by hand and is also equipped with a pre-set mechanical release.

3. Pilot insignia for the VPL

In early June 1955, it was learned that, since 25 May 1955, the VEB Schlossund Metallwarenfabriken Branderburg (metal goods factories) have been working on tools required for the manufacture of metal insignia for the VPL. The insignia, about 12 cm long, all egedly represents 2 intended wings with a round metal disc in the middle. The disc is surrounded by an unsymmetrical oak leaf cluster and a black-red-golden cockade is in the middle of the disc. Both the rim of the disc and the wings are to be beaded.

10	Comment: The present report which dos not furnish new information	·ž	25X1
	summarizes details on initial PL pilot training.	.:	-

2. Comment. This is the first information on the manufacture of VPL insignia. For sketch of insignia, see Annex.

SECRET		
•		

25X1

25X1

